



Figure similar

*** spare part *** SIMATIC DP, connection IM 153-1, for ET 200M, for max. 8 S7-300 modules

General information	
Product type designation	IM 153-1 DP ST
Vendor identification (VendorID)	801Dh
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	not necessary
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	350 mA; At 24 V DC
Inrush current, typ.	2.5 A
I²t	0.1 A²·s
Output voltage	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1 A
Power loss	
Power loss, typ.	3 W
Address area	
Addressing volume	
• Inputs	128 byte
• Outputs	128 byte
Hardware configuration	
number of modules per DP device interface, max.	8
Interfaces	
Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s
1. Interface	
automatic detection of transmission rate	Yes
Interface types	
• Output current of the interface, max.	90 mA
• Design of the connection	9-pin sub D socket
PROFIBUS DP device	
• GSD file	(for DPV1) SIEM801D.GSD; SI01801D.GSG
• automatic baud rate search	Yes

Protocols			
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170		
Protocols (Ethernet)			
• TCP/IP	No		
PROFIBUS DP			
• Number of node addresses, max.	1 to 125 permitted		
Services			
— SYNC capability	Yes		
— FREEZE capability	Yes		
— Direct data exchange (slave-to-slave communication)	Yes; Sender		
Potential separation			
Potential separation exists	Yes		
Isolation			
Isolation tested with	Isolation voltage 500 V		
Degree and class of protection			
IP degree of protection	IP20		
Ambient conditions			
Ambient temperature during operation			
• min.	0 °C		
• max.	60 °C		
• horizontal installation, min.	0 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	0 °C		
• vertical installation, max.	40 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	3 000 m		
Configuration			
Configuration software			
• STEP 7	STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file		
Dimensions			
Width	40 mm		
Height	125 mm		
Depth	117 mm		
Weights			
Weight, approx.	360 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-08
	eClass	12	27-24-26-08
	eClass	9.1	27-24-26-08
	eClass	9	27-24-26-08
	eClass	8	27-24-26-08
	eClass	7.1	27-24-26-08
	eClass	6	27-24-26-08
	ETIM	10	EC001604
	ETIM	9	EC001604
	ETIM	8	EC001604
	ETIM	7	EC001604
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			

[Manufacturer Declaration](#)



[Miscellaneous](#)

[China RoHS](#)



General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



For use in hazardous locations

[FM](#)



[Miscellaneous](#)

[CCC-Ex](#)

Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

[CCS \(China Classification Society\)](#)

last modified:

7/31/2025